U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

ELEVATION CERTIFICATE

IMPORTANT: Follow the instructions on pages 1-9.

OMB No. 1660-0008 Expiration Date: July 31, 2015

SECTION A – PROPERTY INFORMATION					FOR INSURANCE COMPANY USE		
A1. Building Owner's Name BRIAN HESTER					Policy Number:		
A2. Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or PO. Route and Box No. 1209 NORTH RAMSEY					Company NAIC Number:		
City STILLWATER		State	UN		P Code 7	4074	
A3. Property Description (Lot and Block Numbers Tax Parcel Number Legal Description, etc.) LOT 9, BK.2, PAYNE'S SUBDIVISION OF LOT 6, BURR'S ADDITION							
A4. Building Use (e.g., Residential, Non-Residential, Addition, Accessory, etc.) RESIDENTIAL A5. Latitude/Longitude: Lat. N 36 08 05							
SECTION B – FLOOD INSURANCE RATE MAP (FIRM) INFORMATION							
B1. NFIP Community Name & Community Numb	er	B2. County Name	, by,	YNE		B3. State OK	
	, , , , , , , , , , , , , , , , , , , ,		B7, FIRM Panel Effective/ Revised Date N/A B8. F		AO, u	B9. Base Flood Elevation(s) (Zone A0, use base flood depth) 893.7	
B10. Indicate the source of the Base Flood Elevation (BFE) data or base flood depth entered in Item B9:							
XXFIS Profile							
C1. Building elevations are based on: Construction Drawings* Building Under Construction* *A new Elevation Certificate will be required when construction of the building is complete. C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/AE, AR/A1–A30, AR/AH, AR/AO. Complete Items C2.a-h below according to the building diagram specified in Item A7. In Puerto Ricc only, enter meters. Benchmark Utilized: SW17 Vertical Datum: VERTCON TO NAVD 88							
Indicate elevation datum used for the elevations in items a) through h) below. Datum used for building elevations must be the same as that used for the BFE.							
a) Top of bottom floor (including basement, crawlspace, or enclosure floor) 893.3				Check the measurement used. XXeet ☐ meters			
b) Top of the next higher floor		96.2	XXfeet	meters			
c) Bottom of the lowest horizontal structural member (V Zones only)			<u>/A</u>	feet	meters		
d) Attached garage (top of slab)			NE	XXfeet	☐ meters		
e) Lowest elevation of machinery or equipment servicing the building							
f) Lowest adjacent (finished) grade next to building (LAG)			3.3	XXfeet	meters		
g) Highest adjacent (finished) grade next to building (HAG)							
SECTION I	D - SURVEYOR, EN	GINEER, OR A	RCHITEC	T CERTIFICATIO	N	THE RESERVE OF THE PARTY OF THE	
This certification is to be signed and sealed by a linformation. I certify that the information on this Ct I understand that any false statement may be punit. XXheck here if comments are provided on back to Check here if attachments.	ertificate represents my shable by fine or impriso of form. Were lati	y best efforts to in sonment under 18 itude and longitud	terpret the U.S. Code, e in Section	data available. Section 1001.	on	0.00	
Certifier's Name JIMMY W. HILL		License Number PE 6156			PLACE /		
Title PROFESSIONAL ENGINEER	Name PRIVA				HERE		
Address 2700 S. WESTERN	City ST	ILLWATER	State	OK ZIP Code740	74		
Signature JULY 5, 2016 Telephone 405-743-4455							

FEMA Form 086-0-33 (7/12)

See reverse side for continuation.

Replaces all previous editions.



Certification of Engineered Flood Openings

In accordance with NFIP, FEMA TB 1-08, and ASCE/SEI 24-05

I hereby certify that the Crawl Space Door Systems flood vents 816C5, 1220C5, 1232C5, 1616C5, 1624C5, 1632C5, 2032C5, 2424C5, and 2436C5 are designed in accordance with the requirements of the NFIP "Flood Insurance Manual" (2011) to provide automatic equification of hydrostatic flood forces by allowing for the entry and exit of floodwaters, when properly installed and sized as set forth below. This certification follows the design requirements and specifications established in FEMA Technical Bulietin 2-08, "Openings in Foundation Walls and Walls of Enclosures Below Elevated Buildings in Special Flood Hazard Areas", and the ASCE Standard for "Flood Resistant Design and Construction" (ASCE/SEI 24-05).

Design Characteristics

Section 2.6.2.2 of ASCE 24 provides an equation to determine the required net area of engineered openings (A_o) for a given enclosed area (A_e). This equation is based on the hydraulic formula for the flow rate across sharp edged orifices. I have utilized this equation to calculate 1) the respected flow rate through the individual openings between louvers; 2) the flow rate through the main frame opening in case the louver is blown out during a flood event; and 3) the flow rate of water flowing through louver blades following hydraulic short tube theory. The ultimate maximum total enclosed area (A_e) that can be serviced by a single vent has then been determined by utilizing the lowest flow rate of the three assessed scenarios for each vent and is listed in Table 1.

These values are based on the following assumptions:

- In absence of reliable data, the rates of rise and fall have been assumed with 5 feet/hour;
- The (maximum) difference between the exterior and interior floodwater levels has been assumed with 1 foot during base flood conditions;
- A factor of sufety of 5 has been assumed, which is consistent with design practices related to protection of life and property;
- The net area of openings (A_o) as provided by the manufacturer.

aliation Requirements and Limitations

This certification will be voided if the following installation regularments and limitations are not enforced:

- There shall be a minimum of two openings on different sides of each enclosed area;
- The bottom of each required opening shall be no more than 1ft above the adjacent ground level;
- Table 1 Maximal total enclosed area (A_e) that can be served by each individual model based on the given net area of engineered openings (A_o)

 $H \times W$

lini

8 x 16

12 x 20

12 x 32

16 x 16

16 x 24

16 x 32

20 x 32

24 x 24

24 x 36

[in']

105

235

305

180

310

405

630

570

850

Model

816CS

1220CS

1232CS

1616CS

1624CS

1532CS

2032CS

2424CS

2436CS

No temporary (e.g. during cold weather) or permanent solid cover may be placed into or over the flood vent that would block
the automatic entry or exit of floodwaters at any time;

Where analysis indicates rates of rise and fall greater than 5 ft/hr, the total enclosed area as given in Table 1 shall be reduced accordingly to account for the higher rates of rise and fall.

tabunification of the Building and Installed Flood Vents

The Bood vent models marked in Table $f 1^*$) are being installed at the following building:

Sianature

saliding Address

1209 N. Ransex

Stillwoter, OK

ilylag Sesig<mark>n Professional</mark>

Wante Coristopher Wark Loney

Weshamical Engineer


Address 1575 Microdith Road, Virginia Beach, VA 23455

of LEGIES Surfacionary Engineers

of Cicense Professional Engineer

License # 0402029000

assuing Store Virginia



[ft2]

205

500

355

01

1

1244

1230

1765